

ZUIGNAPPEN
VACUUM CUPS

VLAkke
FLAT | **VSP**



SPECIFICATIES · CHARACTERISTICS

Ø Onbelast / Ø belast	Ø unloaded / Ø loaded	[mm]
Minimale buig radius	Minimum curve radius	[mm]
Maximale slag	Maximum stroke	[mm]
Volume	Volume	[cm³]
Gewicht	Weight	[g]
Kracht -0,4 bar	Force at -0,4 bar	[Kgf]
Kracht -0,6 bar	Force at -0,6 bar	[Kgf]
Kracht -0,8 bar	Force at -0,8 bar	[Kgf]
Kracht -0,9 bar	Force at -0,9 bar	[Kgf]

BESTELLEN · HOW TO ORDER

● EPDM zuignap met fitting
vacuum cup with fitting

GESCHIKT VOOR
SUITABLE FOR



Horizontale handeling
Horizontal handling

Gladde oppervlakte
Smooth surfaces

VOORDELEN
ADVANTAGES











Geen markering op oppervlakte
No surface marks

Ø 40

Ø 60

Ø 80

Ø 100



40 / 40

61 / 61

81 / 81

101 / 101

50

80

125

250

2

3

4

4,5

2,77

7,36

14,0

23,4

27

30

53

60

3,68

7,00

7,88

9,68

4,78

7,92

9,85

12,0

5,70

9,41

11,5

13,3

6,31

10,1

12,2

14,8

VSP40EPDM

VSP60EPDM

VSP80EPDM

VSP100EPDM

