

Pressure regulator

pneuparts
.com

PN 60

For high pressure regulator

Version:

Self-relieving piston type regulator (with secondary vent)

Materials:

Bodies: Brass, seals: NBR

Temperature range:

-10°C bis +90°C

Input pressure:

max. 60 bar

Pressure gauge connection:

G 1/4"

Switch panel thread:

DR 2260: M 28 x 1,5

Scope of delivery:

Pressure regulator incl. 50 mm pressure gauge

Advantages:

- Automatic venting in the event of overpressure on the secondary side

** measured at P1 = 20 bar, P2 = 10 bar, Delta p = 4 bar*



HOW TO ORDER: Click on the article numbers to order

Article nr.	Thread	Flow	Pressure regulation area	Pressure gauge display
HPR2260G	G 3/8"	1400 l/min	0.5 - 6 bar	0 - 10 bar
HPR226020G	G 3/8"	1400 l/min	0.5 - 10 bar	0 - 16 bar
HPR226035G	G 3/8"	1400 l/min	0.5 - 16 bar	0 - 25 bar
HPR226050G	G 3/8"	1400 l/min	0.5 - 25 bar	0 - 40 bar
HPR5560G	G 1"	5000 l/min	0.5 - 6 bar	0 - 10 bar
HPR556020G	G 1"	5000 l/min	0.5 - 10 bar	0 - 16 bar
HPR556035G	G 1"	5000 l/min	0.5 - 16 bar	0 - 25 bar
HPR556050G	G 1"	5000 l/min	0.5 - 25 bar	0 - 40 bar

Pneuparts.com
Florijn 10 b/c
5751 PC Deurne
Nederland

Phone: +31 (0)493 763 993
info@pneuparts.com
www.pneuparts.com

BTW: NL8209.12.931B01
KvK: 17126382
Swift: RABONL24
IBAN: NL23RABO01036.31240