

ISO 6432 cylinder, double-acting, diameter 10, stroke 25

Materials:

- End caps: Anodized aluminum, cylinder tube: SS 1.4301, piston rod: SS 1.4305, seal: NBR / PUR

Temperature range:

- -20°C to +80°C

Operating pressure:

- Max. 10 bar

Execution:

- with magnetic piston

Optional:

- Available with different seals for different temperature ranges.
- Call us if you have questions about the other options.

1:1 interchangeable with:

- Festo - DSNU series
- SMC - C85 series
- Norgren - RM series
- Aventics - MNI series
- Parker - P1A series

Made in EU



MCD1025

Cylinder

Iso 6432 cylinder, double-acting, diameter 10, stroke 25

Cylindre

Iso 6432 cylinder, double-acting, diamètre 10, stroke 25

Zylinder

Iso 6432 cylinder, double-acting, durchmesser 10, stroke 25

Pneuparts Code	Piston diameter	Stroke	Search term Festo	Search term SMC	Search term Norgren	Search term Parker	Search term Emerson (Aventics)
MCD1025	10	25	DSNU-10-25	C85B10-25	RM/8010/25	P1A-B010M N0025	MNI-010-002 5

Pneuparts Code	Name	Piston diameter	Stroke	Piston rod thread	Pressure force at 7 bar	Air connection	Weight
MCD1025	ISO 6432 cylinder, double-acting, diameter 10, stroke 25	10	25	M 4 x 0.7	5.5	M 5	50

ISO 6432 cylinder, double-acting, diameter 10, stroke 25

Related Accessories

Pneuparts Code:	MCD1025
Achterscharnier:	BG810ST
Achterscharnier, RVS:	BG810SS
Voetbevestiging:	BF810ST
Voetbevestiging, RVS:	BF810SS
Flensbevestiging:	BFL810ST
Flensbevestiging, RVS:	BFL810SS
Beugel bevestiging:	NT10
Flexor koppeling:	FC810ST
Flexor koppeling, RVS:	FC810SS
Gaffel met pen:	YH810ST
Gaffel met pen, RVS:	YH810SS
Kogelstangkop:	SH810ST
Kogelstangkop, RVS:	SH810SS