

# ANGLE SCREWED CONNECTIONS

## Nickel-plated brass

### Materials:

Body: nickel-plated brass, cutting ring: brass

### Temperature range:

-60°C up to max. +300°C (swivel screw connections: -20°C up to max. +80°C)

### Recommended raw materials:

Copper, polyamide (with reinforced sleeve)

### Note:

When using soft copper tube a correction factor of 0.65 must be used (pressure x 0.65). When using polyamide tube the operating pressure of the tube applies.



Article nr.	Hose/tube Ø external (mm)	Female Thread (G)	Version
ECRF4LLRMSV	4	R 1/8"	Very light model series
ECRF6LLRMSV	6	R 1/8"	Very light model series
ECRF6LLR14MSV	6	R 1/4"	Very light model series
ECRF8LLRMSV	8	R 1/8"	Very light model series
ECRF8LLR14MSV	8	R 1/4"	Very light model series
ECRF8LLR38MSV	8	R 3/8"	Very light model series
ECRF10LRMSV	10	R 1/4"	Light model series
ECRF10LR38MSV	10	R 3/8"	Light model series
ECRF12LRMSV	12	R 3/8"	Light model series
ECRF12LR12MSV	12	R 1/2"	Light model series
ECRF15LR12MSV	15	R 1/2"	Light model series
ECRF18LRMSV	18	R 1/2"	Light model series