pneuparts .com

Pressure switch

MDR 4

With diaphragms for compressors

Pressure switch with start-stop function for controlling compressors.

Fixed pressure difference of approximately between minimum and maximum pressure. The pressure regulator, is ideal to include. pressure gauge, pressure regulator, safety valve to be connected

FUhYX"]bgi`Uh]cbʻjc`hU[Y Í€€ÁX

A chcf`gk]hVY]b[`WUdUVIjhm 2.5 \ Y

6 ifgh]b[ʻghfYb[h\ NÁ∺ÍÁàæ¦

DYfa]gg]V`Y`aYX]ia`hYadYfUhifY ËÅ⊞ËÅ€Á¢Ô


DYfa]gg]V`Y`a YX]ia `HYa dYfUhifY`k UHYf É⁄&0ÁÔ


5]fžkUhYf

Ü^∙ãrœ);c

- 3-phase
- Switching capacity 4.0 / 5.5 kW
- Max. cut-out pressure 16 bar
- 3-pole
- 4-way-flange (optional)







Pneuparts.com

Florijn 10 b/c 5751 PC Deurne Nederland Phone: +31 (0)493 763 993

info@pneuparts.com www.pneuparts.com BTW: NL8209.12.931B01 KvK: 17126382 Swift: RABONL24 IBAN: NL23RABO01036.31240

pneuparts .com

Pressure switch

MDR 5

With diaphragms for compressors

Ú¦^••`¦^Á; ã&@Á; ão@Á; cæbdë:d[]Á`}&cā;}Á{; ¦Á&[}d[||ā;*Á &[{];^••[;+È

Øã¢^åÁ,¦^••`¦^Áåã-^¦^}&^Á; Áġġ]]¦[¢ã[aœc^|^Áå^ç, ^^}Á {ĝã[`{ÁœjåÁ[aœcã[`{Áj,¦^••`¦^ÈV@Aj,¦^••`¦^Á !^*`|æ@[¦Ê£ásÁåå^æ¢Á[Á3j,&]`å^ÈAj,¦^••`¦^Á*æ`*^ÊÂ]¦^••`¦^Á^*`|æ@[¦Ê4;æ^ćÁşæç^Á(j,Áa^Á&[}}^&cå

FUHYX']bgi`Uh]cb'jc`HU[Y Í€€ÁX

Achcf`gk]hW[]b[`WUdUW]hm G∄∖Y

6 i fgh]b[ˈɡhfYb[h NÁ40 àæ¦

DYfa]gg]V`Y`aYX]ia`hYadYfUhifY EÁ⊞ÉÁ€ÁÔ


DYfa]gg]V`Y`aYX]ia`HYadYfUhifY`kUhYf É€ÁxÔ

5]fžkUhYf

Ü^∙ãrœ);c

ÂÛğ * |^ Á; @ • ^
ÂÛ, ã& @; * & æ; æ&ã: ÁCÈÁ Y
ÂT æÈ\$ čţ ` ´A; |^ • • • ` |^ ÁFG\$ #
ÁCË [|^ ÁÇ>ÊÒÈ
ÁCE\$ ÁOÞÂ €J | Ï





Pneuparts.com

Florijn 10 b/c 5751 PC Deurne Nederland Phone: +31 (0)493 763 993

info@pneuparts.com www.pneuparts.com BTW: NL8209.12.931B01 KvK: 17126382 Swift: RABONL24 IBAN: NL23RABO01036.31240