

PNEUDRAIN HP S

High-pressure time-controlled condensate drain with stainless steel valve

PRODUCT FEATURES

The PNEUDRAIN HPS is designed to remove condensate from high pressure compressed air systems and systems that require stainless steel valves (i.e. food industry, etc.) - up to 500 bar.

The PNEUDRAIN HP S offers true installation simplicity and trouble free condensate draining on systems up to 500 bar, depending on the valve orifice, valve material and seal selection. It is recognised as the most reliable and best performing condensate drain worldwide.



COMMERCIAL BENEFITS

- Suitable for all types of compressed air systems up to 500 bar
- Special valve constructions & seals available for special applications
- Stainless steel valve options, offering you solutions in niche markets
- Serviceable valve construction, offering you routine maintenance revenues
- Consult JORC for private labelling options

TECHNICAL ADVANTAGES

- Brass & stainless steel valve constructions depending on pressure
- FPM, Peek, PU, NBR and several other seals are available
- Does not air-lock during operation
- Quick to service
- TEST (micro-switch) feature

Pneuparts.com Florijn 10 b/c 5751 PC Deurne

Nederland

Phone: +31 (0)493 763 993

info@pneuparts.com www.pneuparts.com BTW: NL8209.12.931B01 KvK:

17126382

Swift: RABONL24

IBAN: NL23RABO01036.31240



DIMENSIONS









Stainless steel valve options, offering you solutions in niche markets

TECHNICAL SPECIFICATIONS

Max. compressor capacity Any size

Pressure range O - 500 bar (depending on PNEUDRAIN model) 1 Supply voltage options 2 - 380 VAC/DC 50/60HZ. (please indicate)

Medium temperature 1-55 °C Ambient temperature 1-55 °C

Timer cycle range (On/OFF) 0.5 - 10 seconds / 0.5 - 45 minutes **Timer PCB** SMD technology, ensuring consistency

in production

Timer cycle indication **Bright LED illumination**

TEST feature Yes

Valve type 2/2 way, direct acting Valve orifice Depending on pressure

Valve seals FPM, Peek, PU, NBR (depending on pressure) 1/4"

BSP or NPT Inlet/outlet connections

1 cm Inlet connection height Serviceable valve Yes

Valve housing material Brass and Stainless steel valve constructions,

depending on pressure

Phone: +31 (0)493 763 993

Power connection DIN 43650-A **Environmental**

IP65 (NEMA4)



The right seal for the right job!



Highest quality PCB

NEN - EN - ISO 9001:2015 certified

Information provided herewith is believed to be accurate and reliable. However, no responsibility is assumed for its use or for any infringement of patents or rights of others, which may result from its use.



Pneuparts.com

protection

Florijn 10 b/c 5751 PC Deurne

info@pneuparts.com Nederland www.pneuparts.com BTW: NL8209.12.931B01 KvK:

17126382

Swift: RABONL24

IBAN: NL23RABO01036.31240