

PNEUDRAIN COMBO

Electronic timer drain with integrated strainer

PRODUCT FEATURES

The PNEUDRAIN-COMBO timer controlled condensate drain is a combination of a solenoid valve and an electronic timer designed to automatically remove condensate from compressors, compressed air dryers and receivers - up to 16 bar applications.

The PNEUDRAIN-COMBO saves installation time and protects against large particles found in condensate, thanks to the integrated ball valve and strainer. The unit can be shut off from the compressed air system, enabling easy and safe work to be carried out.



COMMERCIAL BENEFITS

- Installation time saver thanks to the integrated shut off valve and mesh strainer
- Dual thread inlet (1/2" & 1/4"), offering installation flexibility
- Any type of compressed air system and up to 16 bar
- Serviceable valve construction, offering you routine maintenance revenues

TECHNICAL ADVANTAGES

- Integrated mesh strainer, offering valve and orifice protection from larger particles found in condensate
- Integrated shut off valve, offering easy shut off of the valve for routine maintenance
- Does not air-lock during operation
- TEST (micro-switch) feature

Pneuparts.com Florijn 10 b/c 5751 PC Deurne

Nederland

Phone: +31 (0)493 763 993

info@pneuparts.com www.pneuparts.com

BTW: NL8209.12.931B01 KvK:

17126382

Swift: RABONL24

IBAN: NL23RABO01036.31240



DIMENSIONS





Compact design!

TECHNICAL SPECIFICATIONS

Max. compressor capacity Any size

Pressure range 0 - 16 bar (higher pressure available, see PNEUDRAIN HP) Supply voltage options 12 - 380 VAC/DC 50/60Hz. (please indicate)

Medium temperature 1 - 55 °C Ambient 1 - 55 °C

temperature

Timer cycle range (On/OFF) 0.5 - 10 seconds / 0.5 - 45 minutes
Timer PCB SMD technology, ensuring consistency

in production

Timer cycle indication Bright LED illumination

TEST feature Yes

Valve type 2/2 way, direct acting

Valve orifice 4 mm Valve seals FPM

Inlet/outlet connections 1/4" & 1/2" / 1/2" BSP or NPT

Inlet connection height 1 cm Serviceable valve Yes Valve housing material Brass

Power connection DIN 43650-A Environmental protection IP65 (NEMA4)



Dual inlet feature 1/2" & 1/4"



Integrated mesh strainer

NEN - EN - ISO 9001:2015 certified

Information provided herewith is believed to be accurate and reliable. However, no responsibility is assumed for its use or for any infringement of patents or rights of others, which may result from its use. In addition, Pneuparts reserves the right to revise information without notice and without incurring any obligation.



Pneuparts.com Phone: +31 (0)493 763 993 BTW: NL8209.12.931B01

Florijn 10 b/c

5751 PC Deurne info@pneuparts.com Nederland www.pneuparts.com KvK: 17126382 Swift: RABONL24

IBAN: NL23RABO01036.31240