

3/2 electrically operated valves

Pneuparts valves - monostable

3/2 Operated

DESCRIPTION

Pressure control range:

2 - 8 bar

Function:

3/2 valve

Temperature range:

-5°C to max. +50°C

Switch-on time:

50 ms

Control voltage:

110V AC, 220V (50/60 Hz), 24V DC

Power consumption:


Equal current: 2 W, AC: 4.8/4.4 VA, 6/4.9 VA

Version:

Monostable

Stress tolerance:

+/- 10%



ARTICLE CODE	THREAD	VOLTAGE	FLOW	POWER CONSUMPTION
32SV14M24VDC	G 1/4"	24V DC	980 l/min	2 W
32SV14M24VDC0	G 1/4"	24V DC	980 l/min	2 W
32SV14M24VDCLED	G 1/4"	24V DC	980 l/min	2 W
32SV14M220VAC	G 1/4"	220V AC	980 l/min	6 / 4.9 VA
32SV38M24VDC	G 3/8"	24V DC	1361 l/min	2 W
32SV38M220VAC	G 3/8"	220V AC	1361 l/min	6 / 4.9 VA
32SV12M24VDC	G 1/2"	24V DC	1633 l/min	2 W
32SV12M220VAC	G 1/2"	220V AC	1633 l/min	6 / 4.9 VA