

Straight screw connections

with cylindrical thread

pneuparts
.com

Nickel plated Brass

TECHNICAL FEATURES

Materials:

Nickel plated Brass

Operating pressure:

-0.95 to 20 bar

Temperature range:

-20°C to max. +80°C, with FKM sealing up to
max. +150°



ARTICLE NUMBER	THREAD	HOSE/TUBE	WEIGHT
SC53MSV	M5	4.3x3	6.8
SC553MSV	M5	5x3	6.1
SC54MSV	M5	6x4	7.4
SC186MSV	G 1/8"	8x6	29
SC183MSV	G 1/8"	4.3x3	12
SC184MSV	G 1/8"	6x4	15
SC188MSV	G 1/8"	10x8	24
SC144MSV	G 1/4"	6x4	20
SC146MSV	G 1/4"	8x6	22

ARTICLE NUMBER	THREAD	HOSE/TUBE	WEIGHT
SC148MSV	6	G 1/4"	11.5
SC149MSV	G 1/4"	11.6x9	30g
SC384MSV	G 3/8"	6x4	28g
SC386MSV	G 3/8"	8x6	29g
SC388MSV	G 3/8"	10x8	32g
SC389MSV	G 3/8"	11.6x9	34g
SC3810MSV	G 3/8"	12x10	36g
SC126MSV	G 1/2"	8x6	45g
SC128MSV	G 1/2"	10x8	48g

Pneuparts.com
Florijn 10 b/c
5751 PC Deurne
The Netherlands

Phone: +31 (0)493 763 993

info@pneuparts.com
www.pneuparts.com