


Multi 20 Hot water hose

Electrically conductive

Suitable for air, cold and hot water, and various chemicals.

ITEM DESCRIPTION

Material:
Internal: Black EPDM
Reinforcement: Synthetic fibers
External: Black EPDM



Temperature range:
 -30 °C to max. 100 °C

Working pressure: 20
 bar

Hose length:
 1 and 40 meters

The Multi 20 Hot water hose, is a versatile industrial hose specifically engineered for the discharge of hot water and mild chemicals in demanding environments. Constructed with high-grade EPDM rubber, it offers exceptional resistance to heat, weathering, and ozone aging. It is characterized by its ability to handle a consistent working pressure of 20 bar, making it a reliable choice for professional cleaning and industrial cooling.

| Productcode | Internal Ø | Outside Ø | WD BAR | BD BAR | Bending radius mm | Hose Length |
|-------------|------------|-----------|-----------|-----------|-------------------------|----------------|
| MHH13X211M | 13 | 21 | 20 | 80 | 40 | 1 |
| MHH13X2140M | 13 | 21 | 20 | 80 | 40 | 40 |
| MHH16X241M | 16 | 24 | 20 | 80 | 100 | 1 |
| MHH16X2440M | 16 | 24 | 20 | 80 | 100 | 40 |
| MHH19X281M | 19 | 28 | 20 | 80 | 115 | 1 |
| MHH19X2840M | 19 | 28 | 20 | 80 | 115 | 40 |
| MHH25X351M | 25 | 35 | 20 | 80 | 150 | 1 |
| MHH25X3540M | 25 | 35 | 20 | 80 | 150 | 40 |