

Reducing T-piece Female

Pneuparts

Chrome-nickel-molybdenum stainless steel 1.4401(EN10088).

Pneuparts system pipe/pipe is suitable for closed installations in which corrosion is not an issue. For applications, such as compressed air, these system pipes come in a stainless steel (RVS) version.

Safe and durable connections are the most important goal in during installation of a compressed air system. In addition, quick and easy assembly is important for the installer.

Reliable: By pressing the press fitting and pipe, the required mechanical strength is achieved. Permanent hydraulic tightness is obtained through the springy action of the O-ring.

Double safety: Due to the special design of the O-ring, the fittings leak during the pressure test, preventing future damage during use. Not pressed is not tight In addition, the colored pressure indicators that each fitting has are immediately visible whether it has already been pressed or not. The pressing indicator is released as soon as the fitting has been pressed.

Material:

Chrome-nickel-molybdenum stainless steel 1.4401(EN10088).

Diameter (D) mm:

15 - 108

Thread (G):

G 1/2" - G 2"

- Press indicator
- Not pressed not tight, C-steel
- Zinc-plated outside/ LABS free
- Sealing ring CIIR black/ FKM blue
- Press socket with transparent protective cap
- Fixing: press-press-press



See the next page for the dimensions

Pneuparts.com

Florijn 10 b/c
5751 PC Deurne
Nederland

Phone: +31 (0)493 763 993
info@pneuparts.com
www.pneuparts.com

| ARTICLE NR. | Diameter D & D1 mm | Draad (G) |
|-------------|--------------------|-----------|
| PTD151215SS | 15 - 15 | G 1/2" |
| PTD181218SS | 18 - 18 | G 1/2" |
| PTD183418SS | 18 - 18 | G 3/4" |
| PTD221222SS | 22 - 22 | G 1/2" |
| PTD223422SS | 22 - 22 | G 3/4" |
| PTD281228SS | 28 - 28 | G 1/2" |
| PTD283428SS | 28 - 28 | G 3/4" |
| PTD281028SS | 28 - 28 | G 1" |
| PTD351235SS | 35 - 35 | G 1/2" |
| PTD353435SS | 35 - 35 | G 3/4" |
| PTD351035SS | 35 - 35 | G 1" |
| PTD421242SS | 42 - 42 | G 1/2" |

| ARTICLE NR. | Diameter D & D1 mm | Draad (G) |
|---------------|--------------------|-----------|
| PTD423442SS | 42 - 42 | G 3/4" |
| PTD421042SS | 42 - 42 | G 1" |
| PTD541254SS | 54 - 54 | G 1/2" |
| PTD543454SS | 54 - 54 | G 3/4" |
| PTD541054SS | 54 - 54 | G 1" |
| PTD542054SS | 54 - 54 | G 2" |
| PTD763476SS | 76.1 - 76.1 | G 3/4" |
| PTD762076SS | 76.1 - 76.1 | G 2" |
| PTD883488SS | 88.9 - 88.9 | G 3/4" |
| PTD882088SS | 88.9 - 88.9 | G 2" |
| PTD10834108SS | 108 - 108 | G 3/4" |
| PTD10820108SS | 108 - 108 | G 2" |

