

# Polyurethane tube

## Mono layer

### self-extinguishing

*Flexible linear tube in self-extinguishing etheral base polyurethane. Product used in applications where welding slag may come into contact with the surface.*

#### Features

Flexible UL94 V2 self-extinguishing ether based polyurethane tube. The high thicknesses of the items in this series ensure good protection in case of accidental and occasional contact with glowing sparks or welding slag.



#### Standard lengths

25-50-100 m

#### Operating temperature:

From -40°C to 60°C

#### Safety factor on working pressure:

3:1

Article nr. _ = Lenth	Inner diameter	Outer diameter	Wall Thickness	Bending radius (mm)	Operating pressure	Length (m)
PU6X25SE_B	2.5	6	1.75	10	27 bar	25 - 50 - 100
PU6X35SE_B	3.5	6	1.25	15	17 bar	50 - 100
PU8X45SE_B	4.5	8	1.75	20	18 bar	25 - 50 - 100
PU8X55SE_B	5.5	8	1.25	30	12 bar	25 - 100
PU10X6SE_B	6	10	2	25	16 bar	25 - 50 - 100
PU10X75SE_B	7.5	10	1.25	45	9 bar	25 - 50 - 100
PU12X8SE_B	8	12	2	40	13 bar	25 - 50 - 100