

3/2 - way solenoid valve

Normally closed - Direct acting

pneuparts
.com

Brass

ITEM DESCRIPTION

Function:

Solenoid valve 3/2 way, Direct, N.C.

Material:

Housing: Brass CW617N Sealing: NBR, FPM, EPDM, PTFE

DN:

1.5 - 3

Coils:


24VDC: Pressure: 0 to 20

230AC: Pressure 0 to 20

KV:

0.07

Pictogram



DESCRIPTION

- Solenoid valve 2 ways, direct acting type.
- Brass body
- Switching-On time 18ms.
- Switching-Off time 23ms.

FEATURES

- Maximum allowable pressure: 45bar*
- Maximum fluid viscosity: 25cSt (mm²/s)
- Ambient temperature: with class F coil: -10°C +55°C
- Above 80°C consult our tech department for the application fine tuning
- Universal mounting position

CONSTRUCTION

- Body: Brass
- Armature tube: Stainless steel Aisi 303
- Plunger and core: Stainless steel 430Fr
- Springs: Stainless steel Aisi 302
- Seal material: NBR - FPM - EPDM - PTFE

OPTIONS

- Manual override
- Others on request

Pneuparts.com

Florijn 10 b/c
5751 PC Deurne
Netherlands

+31 (0)493 763 993
info@pneuparts.com
www.pneuparts.com