

Connection pipes

Rectangular plug H

Connection lines with rectangular plug

Description:

Pre-fabricated connection lines with rectangular plug H (6.7x4.2) on one side and 2 loose cable ends on the other side.

Temperature range:

-5°C to +60°C

Voltage:

max. 60 V DC, max. 3 A

Protection class:

IP 40

Cable:

2 x 0.17 mm² (single wires or with PUR jacket)

Cable layout:

PIN 1 - red, PIN 3 - black, PIN 2 - not assigned

Suitable:

These cables are used preferentially for the connection of Festo valves. You have a selection between a 2-wire PUR cable (only for static applications) or 2 single wires (standard).



Article number	Version	Cable length	Weight
CLCHP05	PUR cable	Industriële norm C	2 & PE
CLCHP1	PUR cable	Industriële norm B	2 & PE
CLCHP25	PUR cable	DIN/EN-A	2 & PE
CLCHP5	PUR cable	Industriële norm C	2 & PE
CLCH05	Single wires (standard)	Industriële norm C	2 & PE
CLCH1	Single wires (standard)	Industriële norm B	2 & PE
CLCH25	Single wires (standard)	DIN/EN-A	2 & PE
CLCH5	Single wires (standard)	Industriële norm C	2 & PE