

2 part air units

Pneuparts model series 2

up to 3500 l/min

Version:

Self-relieving filter regulator with attached lubricator

Materials:

Body: Grivory® (PA 66), spring hood: POM, diaphragms and seals: NBR

Temperature range:

-10°C to max. +50°C

Input pressure:

1.5 - 16 bar (model series 0: 1.5 - 12 bar)

Pressure gauge connection:

G 1/4"

Advantages:

- Easing assembly of individual components using coupling kits within a model series,
- Semi-automatic oil filling by connecting a hose to the bottom on the oil bowl (G 1/8"). When the oil fill button is pressed, oil from the bowl will be sucked through the tube (not for model series 0).

Max. condensate amount:

49 cm³

Switch panel thread:

M 42 x 1,5

Scope of delivery:

Air unit, including 50 mm pressure gauge

Oil metering at 1000 l/min:

approx. 1 - 2 drops/min

Oil supply:

80 cm³

Lubricator reaction limit (at 6 bar):

70 l/min

ATEX:

Operating material without its own potential source of ignition in accordance with Directive 2014/34/EU

Optional:

Version with metal bowl and inspection tube -M, automatic discharge -AM, automatic discharge closed when not pressurised (0 to 16 bar) -AMNC, Safety version: with upstream lockable ball valve and filler valve -Si

