

Straight cutting ring fittings

Nickel-plated brass

pneuparts
.com

Materials:

Body: nickel-plated brass, cutting ring: brass

Temperature range:

-60°C up to max. +300°C (swivel screw connections: -20°C up to max. +80°C)

Recommended raw materials:

Copper, polyamide (with reinforced sleeve)

Note:

When using soft copper tube a correction factor of 0.65 must be used (pressure x 0.65). When using polyamide tube the operating pressure of the tube applies.



Article nr.	Hose/tube Ø external (mm)	Thread (G)	Version
SSC4LLRMSV	4	R 1/8"	Very light model series
SSC6LLRMSV	6	R 1/8"	Very light model series
SSC6LLR14MSV	6	R 1/4"	Very light model series
SSC8LLRMSV	8	R 1/8"	Very light model series
SSC8LLR14MSV	8	R 1/4"	Very light model series
SSC8LLR38MSV	8	R 3/8"	Very light model series
SSC10LRMSV	10	R 1/4"	Light model series
SSC10LR38MSV	10	R 3/8"	Light model series
SSC12LRMSV	12	R 3/8"	Light model series
SSC12LR12MSV	12	R 1/2"	Light model series
SSC15LRMSV	15	R 1/2"	Light model series
SSC18LRMSV	18	R 1/2"	Light model series

Pneuparts.com
Florijn 10 b/c
5751 PC Deurne
Nederland

☎ +31 (0)493 763 99
info@pneuparts.com
www.pneuparts.com