

## Threaded nozzles with tapered thread

Up to 16 bar

### nickel-plated brass

Threaded nozzles with tapered thread, up to 16 bar,  
nickel-plated brass

#### TECHNICAL FEATURES:

| Article nr. | Thread (F) | Ø  | CH | P    | L    |
|-------------|------------|----|----|------|------|
| TNC186MSV   | G 1/8"     | 6  | 12 | 8    | 32,5 |
| TNC187MSV   | G 1/8"     | 7  | 12 | 8    | 32,5 |
| TNC188MSV   | G 1/8"     | 8  | 12 | 8    | 32,5 |
| TNC189MSV   | G 1/8"     | 9  | 12 | 8    | 32,5 |
| TNC1810MSV  | G 1/8"     | 10 | 12 | 8    | 32,5 |
| TNC146MSV   | G 1/4"     | 6  | 14 | 11   | 36   |
| TNC147MSV   | G 1/4"     | 7  | 14 | 11   | 36   |
| TNC148MSV   | G 1/4"     | 8  | 14 | 11   | 36   |
| TNC149MSV   | G 1/4"     | 9  | 14 | 11   | 38   |
| TNC1410MSV  | G 1/4"     | 10 | 14 | 11   | 38   |
| TNC1412MSV  | G 1/4"     | 12 | 14 | 11   | 38   |
| TNC389MSV   | G 3/8"     | 9  | 17 | 11,5 | 38,5 |
| TNC3810MSV  | G 3/8"     | 10 | 17 | 11,5 | 38,5 |
| TNC3812MSV  | G 3/8"     | 12 | 17 | 11,5 | 38,5 |
| TNC3814MSV  | G 3/8"     | 14 | 17 | 11,5 | 38,5 |
| TNC3816MSV  | G 3/8"     | 16 | 17 | 11,5 | 38,5 |
| TNC3817MSV  | G 3/8"     | 17 | 17 | 11,5 | 38,5 |

| Article nr. | Thread (F) | Ø  | CH | P  | L    |
|-------------|------------|----|----|----|------|
| TNC1210MSV  | G 1/2"     | 10 | 22 | 14 | 41   |
| TNC1212MSV  | G 1/2"     | 12 | 22 | 14 | 42   |
| TNC1214MSV  | G 1/2"     | 14 | 22 | 14 | 43   |
| TNC1216MSV  | G 1/2"     | 16 | 22 | 14 | 44   |
| TNC1217MSV  | G 1/2"     | 17 | 22 | 14 | 44   |
| TNC1220MSV  | G 1/2"     | 20 | 22 | 14 | 46   |
| TNC3416MSV  | G 3/4"     | 16 | 27 | 16 | 45   |
| TNC3420MSV  | G 3/4"     | 20 | 27 | 16 | 46.5 |
| TNC3425MSV  | G 3/4"     | 25 | 27 | 16 | 56   |
| TNC1025MSV  | G 1"       | 25 | 34 | 19 | 56   |

