

3/2 - way solenoid valve

Normally closed - Direct acting

pneuparts
.com

G1/8", Brass

ITEM DESCRIPTION

Function:

Solenoid valve 3/2 way, Direct, N.C.

Material:

Housing: Brass CW617N Sealing: NBR, FPM, EPDM, PTFE

Thread:

G1/8"

Coils:


24VDC: Pressure: 0 to 20

230AC: Pressure 0 to 20

KV:

0.07

Pictogram



DESCRIPTION

- Solenoid valve 2 ways, direct acting type.
- Brass body
- Switching-On time 18ms.
- Switching-Off time 23ms.

FEATURES

- Maximum allowable pressure: 45bar*
- Maximum fluid viscosity: 25cSt (mm²/s)
- Ambient temperature: with class F coil: -10°C +55°C
- Above 80°C consult our tech department for the application fine tuning
- Universal mounting position

CONSTRUCTION

- Body: Brass
- Armature tube: Stainless steel Aisi 303
- Plunger and core: Stainless steel 430Fr
- Springs: Stainless steel Aisi 302
- Seal material: NBR - FPM - EPDM - PTFE

OPTIONS

- Manual override
- Others on request

Pneuparts.com

Florijn 10 b/c
5751 PC Deurne
Netherlands

+31 (0)493 763 993
info@pneuparts.com
www.pneuparts.com

ARTICLE SPECIFICATIONS

Article nr.	Thread	Orifice	Kv	Pressure		Function	Voltage	Seal	Temp. range °C
				Min	Max				
MV31815N24DC	G1/8"	1,5	0.07	0 - 20		3/2 NC	24VDC	NBR	-10°C / +90°C
MV31815F24DC				0 - 20			24VDC	FKM	-10°C / +160°C
MV31815E24DC				0 - 20			24VDC	EPDM	-10°C / +160°C
MV31815P24DC				0 - 20			24VDC	PTFE	-10°C / +180°C
MV31815N230AC				0 - 20			230VAC	NBR	-10°C / +90°C
MV31815F230AC				0 - 20			230VAC	FKM	-10°C / +160°C
MV31815E230AC				0 - 20			230VAC	EPDM	-10°C / +160°C
MV31815P230AC				0 - 20			230VAC	PTFE	-10°C / +180°C

DIMENSIONS AND DRAWINGS:

