

ISO 6432 cylinder, double-acting, diameter 10, stroke 100

Materials:

- End caps: Anodized aluminum, cylinder tube: SS 1.4301, piston rod: SS 1.4305, seal: NBR / PUR

Temperature range:

- -20°C to +80°C

Operating pressure:

- Max. 10 bar

Execution:

- with magnetic piston

Optional:

- Available with different seals for different temperature ranges.
- Call us if you have questions about the other options.

1:1 interchangeable with:

- Festo - DSNU series
- SMC - C85 series
- Norgren - RM series
- Aventics - MNI series
- Parker - P1A series

Made in EU



MCD10100

Cylinder

Iso 6432 cylinder, double-acting, diameter 10, stroke 100

Cylindre

Iso 6432 cylinder, double-acting, diamètre 10, stroke 100

Zylinder

Iso 6432 cylinder, double-acting, durchmesser 10, stroke 100

Pneuparts Code	Piston diameter	Stroke	Search term Festo	Search term SMC	Search term Norgren	Search term Parker	Search term Emerson (Aventics)
MCD10100	10	100	DSNU-10-100	C85B10-100	RM/8010/100	P1A-B010M N0100	MNI-010-0100

Pneuparts Code	Name	Piston diameter	Stroke	Piston rod thread	Pressure force at 7 bar	Air connection	Weight
MCD10100	ISO 6432 cylinder, double-acting, diameter 10, stroke 100	10	100	M 4 x 0.7	5.5	M 5	70

ISO 6432 cylinder, double-acting, diameter 10, stroke 100

Related Accessories

Pneuparts Code:	MCD10100
Rear hinge:	BG810ST
Rear hinge, stainless steel:	BG810SS
Foot mounting:	BF810ST
Foot mounting, stainless steel:	BF810SS
Flange mounting:	BFL810ST
Flange mounting, stainless steel:	BFL810SS
Mounting bracket:	NT10
Flexor coupling:	FC810ST
Flexor coupling, stainless steel:	FC810SS
Clevis with pin:	YH810ST
Clevis with pin, stainless steel:	YH810SS
Ball joint rod end:	SH810ST
Ball joint rod end, stainless steel:	SH810SS