

The VanDeurne industrial 2-cylinder 2-stage piston compressor features low-speed pumps. They are equipped with cast iron cylinders and valve plates with intermediate and aftercooler. These powerful compressors are extremely durable and reliable due to the oversized and the low speed famous Chinook pumps.

- Wcf_gdUW
- Mobi`Y`Udd`]WWh]cbg
- 5]f`hcc`g

U

- J c`HU[`Y` 230 en 400 Voltg
- Dck Yf` 1.5kW/2pk en 2.2kW/3pk`
- Cylinder content 50, 100 en 150 liter
- Pressure` 10 bar

O

- @ck `gdYYX
- @cb[``]ZYgdUb
- F cVi gh&! Vn]bXYf`di a d
- FYg]ghUbh`hc` \YUj m`cUXg
- Lck `bc]gY`Yj Y`
- EfficiYnt
- Dck YfZi ``di a dg
- H][\ `ZZYVh]j Y`WUdUV]m



Model*	kW	pk	L/min	Content liter	Bar	Volt	Cil.	Traps	RPM	Size (lxbxh)
VDSM31050L	1,5	2	260	50	10	230	2	1	1000	800x380x750
VDSM31050K	1,5	2	260	50	10	400	2	1	1000	800x380x750
VDSM310100L	1,5	2	260	100	10	230	2	1	1000	1050x400x830
VDSM310100K	1,5	2	260	100	10	400	2	1	1000	1050x400x830
VDSM410100L	2,2	3	400	100	10	230	2	1	1000	1050x400x830
VDSM410100K	2,2	3	400	100	10	400	2	1	1000	1050x400x830
VDSM410150L	2,2	3	400	150	10	230	2	1	1000	1380x440x900
VDSM410150K	2,2	3	400	150	10	400	2	1	1000	1380x440x900

*Click the model number for the most recent (price) information