

# Pneudrain timer

## T - timer

### PRODUCT FEATURES

The PNEUDRAIN timer controlled condensate drain is a combination of a solenoid valve and an electronic timer designed to automatically remove condensate from compressors, compressed air dryers and receivers - up to any size, type or capacity.

The PNEUDRAIN offers installation simplicity and it is recognised as the most reliable and best performing condensate drain worldwide. The large orifice in the direct acting valve, combined with its sophisticated timer module ensure many years of trouble-free draining of condensate providing minimum service work is carried out.

### COMMERCIAL BENEFITS

- Any type of compressed air system and up to any compressor capacity
- Also available in stainless steel and high pressure
- Voltage range 12 – 380VAC/DC
- Environmental low Watt version available
- Serviceable valve construction, offering you routine maintenance revenue

### TECHNICAL BENEFITS

- Large (4.5 mm) valve orifice
- Does not air-lock during operation
- Quick to service
- TEST (micro-switch) feature
- Accurate time cycles
- High quality PCB components, offering you consistent quality



**Pneuparts.com**  
Florijn 10 b/c  
5751 PC Deurne  
The Netherlands

Phone: +31 (0)493 763 993  
info@pneuparts.com  
www.pneuparts.com

BTW: NL8209.12.931B01  
KvK: 17126382  
Swift: RABONL24  
IBAN: NL23RABO01036.31240

## DIMENSIONS



Also available in a version that requires less than 1 Watt to operate!



Highest quality PCB

## TECHNICAL SPECIFICATIONS

Max. compressor capacity	Any size				
Pressure range	0 - 16 bar (higher pressure available)				
Supply voltage options	12 - 380 VAC/DC 50/60Hz. (please indicate)				
Medium	temperature	1	-	55	°C
Ambient temperature		1 - 55 °C			
Timer cycle range (On/OFF)		0.5 - 10 seconds / 0.5 - 45 minutes			
Timer PCB		SMD technology, ensuring consistency in production			
Timer cycle indication		Bright LED illumination			
TEST feature		Yes			
Valve type		2/2 way, direct acting			
Valve orifice		4.5 mm			
Valve seals		FPM			
Inlet/outlet connections		1/8", 1/4", 3/8" or 1/2" BSP or NPT			
Inlet connection height		1 cm			
Serviceable valve		Yes			
Valve housing material		Brass (Stainless steel available)			
Power connection		DIN 43650-A			
Environmental protection		IP65 (NEMA4)			



Accessories include ball valve strainers

EN - EN - ISO 9001:2015 certified

Information provided herewith is believed to be accurate and reliable. However, no responsibility is assumed for its use or for any infringement of patents or rights of others, which may result from its use. In addition.



**Pneuparts.com**  
 Florijn 10 b/c  
 5751 PC Deurne  
 The Netherlands

Phone: +31 (0)493 763 993  
 info@pneuparts.com  
 www.pneuparts.com

BTW: NL8209.12.931B01  
 KvK: 17126382  
 Swift: RABONL24  
 IBAN: NL23RABO01036.31240