

Compressed air hose

Insert wire

PU / PVC Flexible

ITEM DESCRIPTION

Material:

Internal:

Reinforcement:

External:

Black polyurethane/PVC, oil mist resistant

Textile yarn

Blue synthetic elastomer, abrasion and ozone resistant.

Temperature range:

-20 °C to max. 60+ °C

Working pressure: 20

bar

Standards: high-quality compressed air hose that, thanks to its polyurethane (PU) inner tube, is exceptionally resistant to oil mist and wear. With a working pressure of 20 bar and extreme flexibility, it is perfect for intensive use with pneumatic tools in workshops and assembly lines. This hose is primarily used in environments where flexibility and durability are essential, even when exposed to ozone and outdoor weather conditions.

Hose length:

1 and 50 meters



Productcode	Internal Ø	Outside Ø	WD BAR	BD BAR	Bending radius mm	Hose Length
PU6FLEX10	6	10	20	60	24	1
PU6FLEX50	6	10	20	60	24	50
PU8FLEX10	8	12	20	60	32	1
PU8FLEX50	8	12	20	60	32	50
PU10FLEX10	10	15	20	60	40	1
PU10FLEX50	10	15	20	60	40	50
PU13FLEX10	13	19	20	60	52	1
PU13FLEX50	13	19	20	60	52	50
PVC16FLEX10	16	23	20	60	64	1
PVC16FLEX50	16	23	20	60	64	50
PVC19FLEX10	19	26.75	20	60	76	1
PVC19FLEX50	19	26.75	20	60	76	50
PVC25FLEX10	25	33.70	20	60	100	1
PVC25FLEX50	25	33.70	20	60	100	50