

ISO 6432 cylinder, double-acting, diameter 25, stroke 75

Materials:

- End caps: Anodized aluminum, cylinder tube: SS 1.4301, piston rod: SS 1.4305, seal: NBR / PUR

Temperature range:

- -20°C to +80°C

Operating pressure:

- Max. 10 bar

Execution:

- with magnetic piston

Optional:

- Available with different seals for different temperature ranges.
- Call us if you have questions about the other options.

1:1 interchangeable with:

- Festo - DSNU series
- SMC - C85 series
- Norgren - RM series
- Aventics - MNI series
- Parker - P1A series

Made in EU



MCD2575

Cylinder

Iso 6432 cylinder, double-acting, diameter 25, stroke 75

Cylindre

Iso 6432 cylinder, double-acting, diamètre 25, stroke 75

Zylinder

Iso 6432 cylinder, double-acting, durchmesser 25, stroke 75

Pneuparts Code	Piston diameter	Stroke	Search term Festo	Search term SMC	Search term Norgren	Search term Parker	Search term Emerson (Aventics)
MCD2575	25	75	DSNU-25-75	C85B25-75	RM/8025/75	P1A-B025M N0075	MNI-025-0075

Pneuparts Code	Name	Piston diameter	Stroke	Piston rod thread	Pressure force at 7 bar	Air connection	Weight
MCD2575	ISO 6432 cylinder, double-acting, diameter 25, stroke 75	25	75	M 10 x 1.25	34.0	G 1/8"	327

ISO 6432 cylinder, double-acting, diameter 25, stroke 75

Related Accessories

Pneuparts Code:	MCD2575
Rear hinge:	BG2025ST
Rear hinge, stainless steel:	BG2025SS
Foot mounting:	BF2025ST
Foot mounting, stainless steel:	BF2025SS
Flange mounting:	BFL2025ST
Flange mounting, stainless steel:	BFL2025SS
Mounting bracket:	NT25
Flexor coupling:	FC2532ST
Flexor coupling, stainless steel:	FC2532SS
Clevis with pin:	YH2532ST
Clevis with pin, stainless steel:	YH2532SS
Ball joint rod end:	SH2532ST
Ball joint rod end, stainless steel:	SH2532SS