

Straight screwed-in cutting fittings

With female thread, Nickel-plated brass

pneuparts
.com

Materials:

Body: nickel-plated brass, cutting ring: brass

Temperature range:

-60°C up to max. +300°C (swivel screw connections: -20°C up to max. +80°C)

Recommended raw materials:

Copper, polyamide (with reinforced sleeve)

Note:

When using soft copper tube a correction factor of 0.65 must be used (pressure x 0.65). When using polyamide tube the operating pressure of the tube applies.



Article nr.	Hose/tube Ø external (mm)	Thread (G)	Version
SCRF4LRRMSV	4	R 1/8"	Very light model series
SCRF6LRRMSV	6	R 1/8"	Very light model series
SCRF6LRR14MSV	6	R 1/4"	Very light model series
SCRF8LRRMSV	8	R 1/8"	Very light model series
SCRF8LLR14MSV	8	R 1/4"	Very light model series
SCRF8LRR38MSV	8	R 3/8"	Very light model series
SCRF10LRMSV	10	R 1/4"	Light model series
SCRF10LR38MSV	10	R 3/8"	Light model series
SCRF12LRMSV	12	R 3/8"	Light model series
SCRF12LR12MSV	12	R 1/2"	Light model series
SCRF15LRMSV	15	R 1/2"	Light model series
SCRF18LRMSV	18	R 1/2"	Light model series

Pneuparts.com

Florijn 10 b/c
5751 PC Deurne
Nederland

+31 (0)493 763 99
info@pneuparts.com
www.pneuparts.com