

2 part air units

Pneuparts model series 0

up to 800 l/min

Version:

Filtering using the centrifugal principal and sintered filter

Materials:

Body: Grivory® (PA 66), spring hood: POM, diaphragms and seals: NBR

Temperature range:

-10°C to max. +50°C

Input pressure:

1.5 - 16 bar (model series 0: 1.5 - 12 bar)

Pressure gauge connection:

G 1/4"

Advantages:

- Easing assembly of individual components using coupling kits within a model series,
- Semi-automatic oil filling by connecting a hose to the bottom on the oil bowl (G 1/8"). When the oil fill button is pressed, oil from the bowl will be sucked through the tube (not for model series 0).

Oil metering at 1000 l/min: approx. 10 - 20 drops/min

Oil supply:

35 cm³

Lubricator reaction limit (6 bar):

26 l/min

Article code	Thread	Orifice (DN)	Pressure regulation area	Pressure gauge display	Condensate drain
AU0144F	G 1/4"	800 l/min	0.2 - 4 bar	0.2 - 6 bar	Semi-automatic
AU0144FB	G 1/4"	800 l/min	0.2 - 4 bar	0.2 - 6 bar	Semi-automatic
AU014FB	G 1/4"	800 l/min	0.5 - 8 bar	0.5 - 10 bar	Semi-automatic
AU014F	G 1/4"	800 l/min	0.5 - 8 bar	0.5 - 12 bar	Semi-automatic
AU01410F	G 1/4"	800 l/min	0.5 - 10 bar	0.5 - 16 bar	Semi-automatic
AU01410FB	G 1/4"	800 l/min	0.5 - 10 bar	0.5 - 16 bar	Semi-automatic

