

ISO 6432 cylinder, double-acting, diameter 20, stroke 60

Materials:

- End caps: Anodized aluminum, cylinder tube: SS 1.4301, piston rod: SS 1.4305, seal: NBR / PUR

Temperature range:

- -20°C to +80°C

Operating pressure:

- Max. 10 bar

Execution:

- with magnetic piston

Optional:

- Available with different seals for different temperature ranges.
- Call us if you have questions about the other options.

1:1 interchangeable with:

- Festo - DSNU series
- SMC - C85 series
- Norgren - RM series
- Aventics - MNI series
- Parker - P1A series

Made in EU



MCD2060

Cylinder

Iso 6432 cylinder, double-acting, diameter 20, stroke 60

Cylindre

Iso 6432 cylinder, double-acting, diamètre 20, stroke 60

Zylinder

Iso 6432 cylinder, double-acting, durchmesser 20, stroke 60

Pneuparts Code	Piston diameter	Stroke	Search term Festo	Search term SMC	Search term Norgren	Search term Parker	Search term Emerson (Aventics)
MCD2060	20	60	DSNU-20-60	C85B20-60	RM/8020/60	P1A-B020M N0060	MNI-020-0060

Pneuparts Code	Name	Piston diameter	Stroke	Piston rod thread	Pressure force at 7 bar	Air connection	Weight
MCD2060	ISO 6432 cylinder, double-acting, diameter 20, stroke 60	20	60	M 8 x 1.25	22.0	G 1/8"	210

ISO 6432 cylinder, double-acting, diameter 20, stroke 60

Related Accessories

Pneuparts Code:	MCD2060
Rear hinge:	BG2025ST
Rear hinge, stainless steel:	BG2025SS
Foot mounting:	BF2025ST
Foot mounting, stainless steel:	BF2025SS
Flange mounting:	BFL2025ST
Flange mounting, stainless steel:	BFL2025SS
Mounting bracket:	NT20
Flexor coupling:	FC20ST
Flexor coupling, stainless steel:	FC20SS
Clevis with pin:	YH20ST
Clevis with pin, stainless steel:	YH20SS
Ball joint rod end:	SH20ST
Ball joint rod end, stainless steel:	SH20SS